

## Natural Rubber Sheet BS1154 Datasheet

Product Code: RC0345-Y40

### Product Description

Our Natural Rubber Sheet BS1154, as the name suggests, conforms to British standards 1154. Conforming to this requirement means that the product is certifiably good for use in highly demanding applications and environments. Our sheeting features excellent physical properties inclusive of high tensile strength and a good abrasion performance.

### Technical Specification



**Available In -**



Full Rolls



Cut to strip



Bespoke  
Gaskets

Properties	Test Method	Values
Product		BS1154 Natural Rubber Sheeting
Colour		White
Compound		NR
Hardness (Shore A)		40° ± 5°
Density		1.10 g/cm <sup>2</sup>
Tensile Strength		19 Mpa
Elongation at Break		600%
Abrasion Resistance		120 mm <sup>3</sup>
Working Temperature Range		-20°C to +70°C



**ISO  
9001 : 2015  
REGISTERED**

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



*Manufacturers • Designers • Distributors*

Experts in  
**Rubber**

## Standard Sizes

Stock Roll Sizes	Weight (Kg/m <sup>2</sup> )
3mm x 1.4m x 10m	3.3
5mm x 1.4m x 10m	5.5
6mm x 1.4m x 10m	6.6



**ISO**  
**9001 : 2015**  
REGISTERED

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

**E** [sales@therubbercompany.com](mailto:sales@therubbercompany.com) • **W** [www.therubbercompany.com](http://www.therubbercompany.com) • **T** +44 (0) 1794 513 184

The Rubber Company Limited - Registered in England and Wales  
Company Number - 08350831 | VAT Number - GB 156 8355 80

## Natural Rubber Sheet BS1154 Datasheet

Product Code: RC0345-Y50

### Product Description

Our Natural Rubber Sheet BS1154, as the name suggests, conforms to British standards 1154. Conforming to this requirement means that the product is certifiably good for use in highly demanding applications and environments. Our sheeting features excellent physical properties inclusive of high tensile strength and a good abrasion performance.

### Technical Specification



#### Available In -



Full Rolls



Cut to strip



Bespoke  
Gaskets

Properties	Test Method	Values
Product		BS1154 Natural Rubber Sheeting
Colour		White
Compound		NR
Hardness (Shore A)		50° ± 5°
Density		1.15 g/cm <sup>2</sup>
Tensile Strength		17 Mpa
Elongation at Break		500%
Abrasion Resistance		125 mm <sup>3</sup>
Working Temperature Range		-20°C to +70°C



**ISO**  
**9001 : 2015**  
REGISTERED

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



*Manufacturers • Designers • Distributors*

Experts in  
**Rubber**

## Standard Sizes

Stock Roll Sizes	Weight (Kg/m <sup>2</sup> )
3mm x 1.4m x 10m	3.45
5mm x 1.4m x 10m	5.75
6mm x 1.4m x 10m	6.90



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

**E** [sales@therubbercompany.com](mailto:sales@therubbercompany.com) • **W** [www.therubbercompany.com](http://www.therubbercompany.com) • **T** +44 (0) 1794 513 184

The Rubber Company Limited - Registered in England and Wales  
Company Number - 08350831 | VAT Number - GB 156 8355 80

## Natural Rubber Sheet BS1154 Datasheet

Product Code: RC0345-Y60

### Product Description

Our Natural Rubber Sheet BS1154, as the name suggests, conforms to British standards 1154. Conforming to this requirement means that the product is certifiably good for use in highly demanding applications and environments. Our sheeting features excellent physical properties inclusive of high tensile strength and a good abrasion performance.

### Technical Specification



#### Available In -



Full Rolls



Cut to strip



Bespoke  
Gaskets

Properties	Test Method	Values
Product		BS1154 Natural Rubber Sheeting
Colour		White
Compound		NR
Hardness (Shore A)		60° ± 5°
Density		1.2 g/cm <sup>2</sup>
Tensile Strength		17 Mpa
Elongation at Break		400%
Abrasion Resistance		130 mm <sup>3</sup>
Working Temperature Range		-20°C to +70°C



**ISO  
9001 : 2015  
REGISTERED**

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



*Manufacturers • Designers • Distributors*

Experts in  
**Rubber**

## Standard Sizes

Stock Roll Sizes	Weight (Kg/m <sup>2</sup> )
3mm x 1.4m x 10m	3.6
5mm x 1.4m x 10m	6
6mm x 1.4m x 10m	7.2



**ISO**  
**9001 : 2015**  
REGISTERED

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

**E** [sales@therubbercompany.com](mailto:sales@therubbercompany.com) • **W** [www.therubbercompany.com](http://www.therubbercompany.com) • **T** +44 (0) 1794 513 184

The Rubber Company Limited - Registered in England and Wales  
Company Number - 08350831 | VAT Number - GB 156 8355 80

## Natural Rubber Sheet BS1154 Datasheet

Product Code: RC0345-Z40

### Product Description

Our Natural Rubber Sheet BS1154, as the name suggests, conforms to British standards 1154. Conforming to this requirement means that the product is certifiably good for use in highly demanding applications and environments. Our sheeting features excellent physical properties inclusive of high tensile strength and a good abrasion performance.

### Technical Specification



#### Available In -



Full Rolls



Cut to strip



Bespoke  
Gaskets

Properties	Test Method	Values
Product		BS1154 Natural Rubber Sheeting
Colour		Black
Compound		NR
Hardness (Shore A)		40° ± 5°
Density		1.1 g/cm <sup>2</sup>
Tensile Strength		19 Mpa
Elongation at Break		600%
Abrasion Resistance		110 mm <sup>3</sup>
Working Temperature Range		-20°C to +70°C



**ISO**  
**9001 : 2015**  
REGISTERED

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



*Manufacturers • Designers • Distributors*

Experts in  
**Rubber**

## Standard Sizes

Stock Roll Sizes	Weight (Kg/m <sup>2</sup> )
3mm x 1.4m x 10m	3.3
5mm x 1.4m x 10m	5.5
6mm x 1.4m x 10m	6.6
10mm x 1.4m x 5m	11



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

**E** [sales@therubbercompany.com](mailto:sales@therubbercompany.com) • **W** [www.therubbercompany.com](http://www.therubbercompany.com) • **T** +44 (0) 1794 513 184

The Rubber Company Limited - Registered in England and Wales  
Company Number - 08350831 | VAT Number - GB 156 8355 80



## Natural Rubber Sheet BS1154 Datasheet

Product Code: RC0345-Z50

### Product Description

Our Natural Rubber Sheet BS1154, as the name suggests, conforms to British standards 1154. Conforming to this requirement means that the product is certifiably good for use in highly demanding applications and environments. Our sheeting features excellent physical properties inclusive of high tensile strength and a good abrasion performance.

### Technical Specification



#### Available In -



Full Rolls



Cut to strip



Bespoke  
Gaskets

Properties	Test Method	Values
Product		BS1154 Natural Rubber Sheeting
Colour		Black
Compound		NR
Hardness (Shore A)		50° ± 5°
Density		1.15 g/cm <sup>2</sup>
Tensile Strength		17 Mpa
Elongation at Break		500%
Abrasion Resistance		115 mm <sup>3</sup>
Working Temperature Range		-20°C to +70°C



**ISO  
9001 : 2015  
REGISTERED**

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



*Manufacturers • Designers • Distributors*

Experts in  
**Rubber**

## Standard Sizes

Stock Roll Sizes	Weight (Kg/m <sup>2</sup> )
3mm x 1.4m x 10m	3.3
5mm x 1.4m x 10m	5.5
6mm x 1.4m x 10m	6.6



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

**E** [sales@therubbercompany.com](mailto:sales@therubbercompany.com) • **W** [www.therubbercompany.com](http://www.therubbercompany.com) • **T** +44 (0) 1794 513 184

The Rubber Company Limited - Registered in England and Wales  
Company Number - 08350831 | VAT Number - GB 156 8355 80

## Natural Rubber Sheet BS1154 Datasheet

Product Code: RC0345-Z60

### Product Description

Our Natural Rubber Sheet BS1154, as the name suggests, conforms to British standards 1154. Conforming to this requirement means that the product is certifiably good for use in highly demanding applications and environments. Our sheeting features excellent physical properties inclusive of high tensile strength and a good abrasion performance.

### Technical Specification



#### Available In -



Full Rolls



Cut to strip



Bespoke  
Gaskets

Properties	Test Method	Values
Product		BS1154 Natural Rubber Sheeting
Colour		Black
Compound		NR
Hardness (Shore A)		60° ± 5°
Density		1.13 g/cm <sup>2</sup>
Tensile Strength		17 Mpa
Elongation at Break		400%
Abrasion Resistance		120 mm <sup>3</sup>
Working Temperature Range		-20°C to +70°C



**ISO**  
**9001 : 2015**  
REGISTERED

The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.



Manufacturers • Designers • Distributors

Experts in  
**Rubber**

## Standard Sizes

Stock Roll Sizes	Weight (Kg/m <sup>2</sup> )
2mm x 1.4m x 20m	2.26
3mm x 1.4m x 10m	3.39
5mm x 1.4m x 10m	5.65
6mm x 1.4m x 10m	6.78
10mm x 1.4m x 5m	11.3
12mm x 1.4m x 5m	13.56
15mm x 1.4m x 5m	16.95
20mm x 1.4m x 5m	22.6
25mm x 1.4m x 5m	28.26



The information contained on this product information sheet is to be used as guidance. The advice is given in good faith and does not constitute any guarantee or recommendation for suitability. The Rubber Company cannot be held liable for any damage caused by incorrect installation. We hereby reserve the right to change the technical information herewith without notification or prior agreement.

E [sales@therubbercompany.com](mailto:sales@therubbercompany.com) • W [www.therubbercompany.com](http://www.therubbercompany.com) • T +44 (0) 1794 513 184

The Rubber Company Limited - Registered in England and Wales  
Company Number - 08350831 | VAT Number - GB 156 8355 80